



ADVANCED FLUID
MANAGEMENT SOLUTIONS

RAASM S.p.a.

Via Marangoni 33, 36022
S. Zeno di Cassola (VI) Italy
Tel. +39 0424 570891
info@raasm.com

P/N 2011010

Air operated pump s. C20F for oil with 50 kg reservoir (external \varnothing 340÷385 mm), R 50:1 and overpressure reversing valve

AREAS OF USE

Aeronautics, Agriculture, Building and road construction, Chemical industry, Manufacturing industry, Mining industry, Lube trucks and transports, Centralized lubrication, Shipping and offshore, Railway transport

FEATURES

Flow rate	1330 cm ³ /min
Tank capacity	50 ÷ 60 kg
Pressure ratio	50:1
Air inlet connection	G 1/4" (f)
Lubricant outlet connection	G 1/4" (f)
Working temperature	-25 ÷ +60 °C
Lubricant	oils > 40 cSt
Drum internal \varnothing	340 ÷ 385 mm
Pump(R 50:1)	p/n 62674
Drum cover	p/n 10/503
Bung adaptor	-
Minimum level indicator	-
Packing	No. 2 - 0,086 m ³
Net weight	13,4 kg
Gross weight	14 kg



OVERALL DIMENSIONS (mm)

