



ADVANCED FLUID  
MANAGEMENT SOLUTIONS

**RAASM S.p.a.**

Via Marangoni 33, 36022  
S. Zeno di Cassola (VI) Italy  
Tel. +39 0424 570891  
info@raasm.com

## P/N 2011100

Air operated pump s. C20F for oil with 60 kg reservoir with G 2" (f) thread, R 50:1 and overpressure reversing valve

### AREAS OF USE

Aeronautics, Agriculture, Building and road construction, Chemical industry, Manufacturing industry, Mining industry, Lube trucks and transports, Centralized lubrication, Shipping and offshore, Railway transport

### FEATURES

Flow rate	1330 cm <sup>3</sup> /min
Tank capacity	50 ÷ 60 kg
Pressure ratio	50:1
Air inlet connection	G 1/4" (f)
Lubricant outlet connection	G 1/4" (f)
Working temperature	-25 ÷ +60 °C
Lubricant	oils > 40 cSt
Drum internal ø	closed - thread 2"
Pump(R 50:1)	p/n 62674
Drum cover	-
Bung adaptor	p/n 10/14
Minimum level indicator	p/n 39650
Packing	No. 2 - 0,086 m <sup>3</sup>
Net weight	13,4 kg
Gross weight	14 kg



### OVERALL DIMENSIONS (mm)

