



ADVANCED FLUID  
MANAGEMENT SOLUTIONS

**RAASM S.p.a.**

Via Marangoni 33, 36022  
S. Zeno di Cassola (VI) Italy  
Tel. +39 0424 570891  
info@raasm.com

## P/N 2011190

Air operated pump s. C20F for oil with 200 kg reservoir with G 2" (f), R 50:1 and overpressure reversing valve

### AREAS OF USE

Aeronautics, Agriculture, Building and road construction, Chemical industry, Manufacturing industry, Mining industry, Lube trucks and transports, Centralized lubrication, Shipping and offshore, Railway transport

### FEATURES

|                             |                           |
|-----------------------------|---------------------------|
| Flow rate                   | 1330 cm <sup>3</sup> /min |
| Tank capacity               | 200 kg                    |
| Pressure ratio              | 50:1                      |
| Air inlet connection        | G 1/4" (f)                |
| Lubricant outlet connection | G 1/4" (f)                |
| Working temperature         | -25 ÷ +60 °C              |
| Lubricant                   | oils > 40 cSt             |
| Drum internal ø             | closed - thread 2"        |
| Pump(R 50:1)                | p/n 62695                 |
| Drum cover                  | -                         |
| Bung adaptor                | p/n 10/14                 |
| Minimum level indicator     | p/n 39650                 |
| Packing                     | No. 2 - 0,060 m3          |
| Net weight                  | 13 kg                     |
| Gross weight                | 13,8 kg                   |



### OVERALL DIMENSIONS (mm)

