



ADVANCED FLUID  
MANAGEMENT SOLUTIONS

**RAASM S.p.a.**

Via Marangoni 33, 36022

S. Zeno di Cassola (VI) Italy

Tel. +39 0424 570891

info@raasm.com

## P/N 2000425

Motor operated pump s. C20P for oil 230-400 V AC - 50 Hz - 275-480 V AC - 60 Hz with 2 pumping element  $\varnothing$  7 mm, 100 litres reservoir and min level indicator

### AREAS OF USE

Aeronautics, Agriculture, Building and road construction, Chemical industry, Manufacturing industry, Mining industry, Lube trucks and transports, Centralized lubrication, Shipping and offshore, Railway transport

### FEATURES

Flow rate	160 cm <sup>3</sup> /min
Tank capacity	40 l
Lubricant inlet connection	G 1/2" (f)
Lubricant outlet connection	G 3/8" (f)
Dosing piston $\varnothing$	7 mm
Working temperature	-25 ÷ +60 °C
Lubricant	oils > 40 cSt
Supply	230/400 V AC - 50 Hz - 276/480 V AC - 60 Hz
Velocity	1370 ÷ 1640 rpm
Packing	No. 1 - 0,268 m <sup>3</sup>
Net weight	61,3 kg
Gross weight	77,7 kg



### OVERALL DIMENSIONS (mm)

