



ADVANCED FLUID
MANAGEMENT SOLUTIONS

RAASM S.p.a.

Via Marangoni 33, 36022

S. Zeno di Cassola (VI) Italy

Tel. +39 0424 570891

info@raasm.com

P/N 2070215

Motor operated pump s. C20S for grease 230-400 V AC - 50 Hz - 275-480 V AC - 60 Hz 6 poles and 4 pumping element, R 35:1, 30 liters reservoir, min level indicator and overpressure reversing valve

AREAS OF USE

Aeronautics, Agriculture, Building and road construction, Chemical industry, Manufacturing industry, Mining industry, Lube trucks and transports, Centralized lubrication, Shipping and offshore, Railway transport

FEATURES

Flow rate	108 cm ³ /min
Tank capacity	30 l
Reducer ratio	35:1
Lubricant inlet connection	G 1/2" (f)
Lubricant outlet connection	G 1/4" (f)
N° of pistons	4
Working temperature	-25 ÷ +60 °C
Compatible fluids	grease max NLGI 2
Supply	230/400 V AC - 50 Hz - 275/480 V AC - 60 Hz
Protection degree	-
Velocity	6 poles: 870 ÷ 1100 rpm
Packing	No. 1 - 0,208 m ³
Net weight	34,7 kg
Gross weight	46,9 kg



OVERALL DIMENSIONS (mm)

