

**P/N 2070230**

Motor operated pump s. C20S for grease 230-400 V AC - 50 Hz - 275-480 V AC - 60 Hz 6 poles and 4 pumping element, R 70:1, 30 liters reservoir, min level indicator and overpressure reversing valve

## AREAS OF USE

Aeronautics, Agriculture, Building and road construction, Chemical industry, Manufacturing industry, Mining industry, Lube trucks and transports, Centralized lubrication, Shipping and offshore, Railway transport

## FEATURES

|                             |                                                |
|-----------------------------|------------------------------------------------|
| Flow rate                   | 56 cm <sup>3</sup> /min                        |
| Tank capacity               | 30 l                                           |
| Reducer ratio               | 70:1                                           |
| Lubricant inlet connection  | G 1/2" (f)                                     |
| Lubricant outlet connection | G 1/4" (f)                                     |
| N° of pistons               | 4                                              |
| Working temperature         | -25 ÷ +60 °C                                   |
| Compatible fluids           | grease max NLGI 2                              |
| Supply                      | 230/400 V AC - 50 Hz -<br>275/480 V AC - 60 Hz |
| Protection degree           | -                                              |
| Velocity                    | 6 poles: 870 ÷ 1100 rpm                        |
| Packing                     | No. 1 - 0,208 m <sup>3</sup>                   |
| Net weight                  | 34,7 kg                                        |
| Gross weight                | 46,9 kg                                        |



### OVERALL DIMENSIONS (mm)

