



ADVANCED FLUID
MANAGEMENT SOLUTIONS

RAASM S.p.a.

Via Marangoni 33, 36022

S. Zeno di Cassola (VI) Italy

Tel. +39 0424 570891

info@raasm.com

P/N 2070530

Motor operated pump s. C20S for oil 230-400 V AC - 50 Hz - 275-480 V AC - 60 Hz 4 poles and 4 pumping element, R 70:1, 30 liters reservoir, min level indicator and overpressure reversing valve

AREAS OF USE

Aeronautics, Agriculture, Building and road construction, Chemical industry, Manufacturing industry, Mining industry, Lube trucks and transports, Centralized lubrication, Shipping and offshore, Railway transport

FEATURES

Flow rate	80 cm ³ /min
Tank capacity	30 l
Reducer ratio	70:1
Lubricant inlet connection	G 1/2" (f)
Lubricant outlet connection	G 1/4" (f)
N° of pistons	4
Working temperature	-25 ÷ +60 °C
Compatible fluids	oils > 40 cSt
Supply	230/400 V AC - 50 Hz - 275/480 V AC - 60 Hz
Protection degree	-
Velocity	4 poles: 1370 ÷ 1660 rpm
Packing	No. 1 - 0,208 m ³
Net weight	34,4 kg
Gross weight	46,6 kg



OVERALL DIMENSIONS (mm)

