



ADVANCED FLUID
MANAGEMENT SOLUTIONS

RAASM S.p.a.

Via Marangoni 33, 36022
S. Zeno di Cassola (VI) Italy
Tel. +39 0424 570891
info@raasm.com

P/N 3023891

Motor operated pump s. C30B18 for grease 24 V DC (PNP - NO) with 1 pumping element, 5 litres reservoir, min level indicator and remote display

AREAS OF USE

Aeronautics, Agriculture, Building and road construction, Chemical industry, Manufacturing industry, Mining industry, Lube trucks and transports, Centralized lubrication, Shipping and offshore, Railway transport

FEATURES

| | |
|------------------------|------------------------------|
| Flow rate | 4,27 cm ³ /min |
| Tank capacity | 5 l |
| Control type | remote |
| Delivery union | G 1/4" (f) |
| Tank filling | by hydraulic greaser |
| N° of pumping elements | 1 |
| Working temperature | -25 ÷ +60 °C |
| Lubricant | grease max NLGI 2 |
| Supply | 24 V DC |
| Protection degree | IP66 |
| Packing | No. 1 - 0,033 m ³ |
| Net weight | 6,2 kg |
| Gross weight | 7,1 kg |



OVERALL DIMENSIONS (mm)

