



ADVANCED FLUID  
MANAGEMENT SOLUTIONS

**RAASM S.p.a.**

Via Marangoni 33, 36022  
S. Zeno di Cassola (VI) Italy  
Tel. +39 0424 570891  
info@raasm.com

## P/N 3070455

Motor operated pump s. C30S for oil 230-400 V AC - 50 Hz - 275-480 V AC - 60 Hz 6 poles and 4 pumping elements, R 35:1, 10 litres reservoir and min level indicator

### AREAS OF USE

Aeronautics, Agriculture, Building and road construction, Chemical industry, Manufacturing industry, Mining industry, Lube trucks and transports, Centralized lubrication, Shipping and offshore, Railway transport

### FEATURES

|                             |                                                |
|-----------------------------|------------------------------------------------|
| Flow rate                   | 108 cm <sup>3</sup> /min                       |
| Tank capacity               | 10 l                                           |
| Reducer ratio               | 35:1                                           |
| Lubricant inlet connection  | G 1/2" (f)                                     |
| Lubricant outlet connection | G 3/8" (f)                                     |
| N° of pistons               | 4                                              |
| Working temperature         | -25 ÷ +60 °C                                   |
| Compatible fluids           | grease max NLGI 2                              |
| Supply                      | 230/400 V AC - 50 Hz -<br>275/480 V AC - 60 Hz |
| Protection degree           | -                                              |
| Velocity                    | 6 poles: 870 ÷ 1100 rpm                        |
| Packing                     | No. 1 - 0,144 m <sup>3</sup>                   |
| Net weight                  | 27,7 kg                                        |
| Gross weight                | 39,5 kg                                        |



### OVERALL DIMENSIONS (mm)

