



ADVANCED FLUID  
MANAGEMENT SOLUTIONS

**RAASM S.p.a.**

Via Marangoni 33, 36022

S. Zeno di Cassola (VI) Italy

Tel. +39 0424 570891

info@raasm.com

## P/N 3070500

Motor operated pump s. C30S for oil 230-400 V AC - 50 Hz - 275-480 V AC - 60 Hz 4 poles and 2 pumping elements, R 70:1, 30 litres reservoir and min level indicator

### AREAS OF USE

Aeronautics, Agriculture, Building and road construction, Chemical industry, Manufacturing industry, Mining industry, Lube trucks and transports, Centralized lubrication, Shipping and offshore, Railway transport

### FEATURES

Flow rate	40 cm <sup>3</sup> /min
Tank capacity	30 l
Reducer ratio	70:1
Lubricant inlet connection	G 1/2" (f)
Lubricant outlet connection	G 3/8" (f)
N° of pistons	2
Working temperature	-25 ÷ +60 °C
Compatible fluids	grease max NLGI 2
Supply	230/400 V AC - 50 Hz - 275/480 V AC - 60 Hz
Protection degree	-
Velocity	4 poles: 1370 ÷ 1660 rpm
Packing	No. 1 - 0,208 m <sup>3</sup>
Net weight	32,8 kg
Gross weight	45 kg



### OVERALL DIMENSIONS (mm)

