



ADVANCED FLUID  
MANAGEMENT SOLUTIONS

**RAASM S.p.a.**

Via Marangoni 33, 36022  
S. Zeno di Cassola (VI) Italy  
Tel. +39 0424 570891  
info@raasm.com

## P/N 1500200

Air operated pump s. C15F for grease with 20 kg reservoir (internal  $\varnothing$  255÷300 mm), R 50:1 and air operated discharging valve

### AREAS OF USE

Aeronautics, Agriculture, Building and road construction, Chemical industry, Manufacturing industry, Mining industry, Lube trucks and transports, Centralized lubrication, Shipping and offshore, Railway transport

### FEATURES

|                             |                              |
|-----------------------------|------------------------------|
| Flow rate                   | 1330 cm <sup>3</sup> /min    |
| Tank capacity               | 20 kg                        |
| Pressure ratio              | 50:1                         |
| Air inlet connection        | G 1/4" (f)                   |
| Lubricant outlet connection | G 3/8" (f)                   |
| Working temperature         | -25 ÷ +60 °C                 |
| Lubricant                   | grease max NLGI 2            |
| Drum internal $\varnothing$ | 255 ÷ 300 mm                 |
| Pump(R 50:1)                | p/n 62548                    |
| Drum cover                  | p/n 10/507                   |
| Membrane                    | p/n 10/63                    |
| Packing                     | No. 2 - 0,089 m <sup>3</sup> |
| Net weight                  | 13,2 kg                      |
| Gross weight                | 13,9 kg                      |



### OVERALL DIMENSIONS (mm)

