



ADVANCED FLUID
MANAGEMENT SOLUTIONS

RAASM S.p.a.

Via Marangoni 33, 36022
S. Zeno di Cassola (VI) Italy
Tel. +39 0424 570891
info@raasm.com

P/N 1501010

Air operated pump s. C15F for oil with 50 kg reservoir (external \varnothing 340÷385 mm), R 50:1 and air operated discharging valve

AREAS OF USE

Aeronautics, Agriculture, Building and road construction, Chemical industry, Manufacturing industry, Mining industry, Lube trucks and transports, Centralized lubrication, Shipping and offshore, Railway transport

FEATURES

Flow rate	1330 cm ³ /min
Tank capacity	50 ÷ 60 kg
Pressure ratio	50:1
Air inlet connection	G 1/4" (f)
Lubricant outlet connection	G 3/8" (f)
Working temperature	-25 ÷ +60 °C
Lubricant	oils > 40 cSt
Drum internal \varnothing	340 ÷ 385 mm
Pump(R 50:1)	p/n 62574
Drum cover	p/n 10/503
Bung adaptor	-
Minimum level indicator	-
Packing	No. 2 - 0,040 m3
Net weight	11,2 kg
Gross weight	11,8 kg



OVERALL DIMENSIONS (mm)

