



ADVANCED FLUID
MANAGEMENT SOLUTIONS

RAASM S.p.a.

Via Marangoni 33, 36022
S. Zeno di Cassola (VI) Italy
Tel. +39 0424 570891
info@raasm.com

P/N 1570050

Motor operated pump s. C15S for grease 230-400 V AC - 50 Hz - 275-480 V AC - 60 Hz 4 poles and 4 pumping elements, R 70:1, 10 litres reservoir, min level indicator and solenoid valve

AREAS OF USE

Aeronautics, Agriculture, Building and road construction, Chemical industry, Manufacturing industry, Mining industry, Lube trucks and transports, Centralized lubrication, Shipping and offshore, Railway transport

FEATURES

Flow rate	80 cm ³ /min
Tank capacity	10 l
Reducer ratio	70:1
Lubricant inlet connection	G 1/2" (f)
Lubricant outlet connection	G 3/8" (f)
N° of pistons	4
Working temperature	-25 ÷ +60 °C
Compatible fluids	grease max NLGI 2
Supply	230/400 V AC - 50 Hz - 275/480 V AC - 60 Hz
Protection degree	-
Velocity	4 poles: 1370 ÷ 1660 rpm
Packing	No. 1 - 0,175 m3
Net weight	31,7 kg
Gross weight	44,5 kg



OVERALL DIMENSIONS (mm)

