



P/N 68213

Trolley mounted pneumatic grease dispenser with 13 kg tanks and pump R 50:1

AREAS OF USE

Aeronautics, Agriculture, Building and road construction, Manufacturing industry, Mining industry, Lube trucks and transports, Centralized lubrication, Railway transport

FEATURES

Delivery hose length 4 m - 1/4" Delivery hose p/n 993.504 Max grease outlet pressure 350 ÷ 400 bar Capacity every 10 cycles of lever - Pump p/n 62041 Compression ratio 50:1 Noise level 81 dB Max working pressure 8 bar Max air consumption 330 l/min Capacity (free outlet 6 bar self-levelling grease at 20 °C) 1000 g/min Grease follower plate yes Grease coupler p/n 66740 Nipple p/n 66892 Grease gun p/n 66888	Tank capacity	13 kg	
Max grease outlet pressure 350 ÷ 400 bar Capacity every 10 cycles of lever - Pump p/n 62041 Compression ratio 50:1 Noise level 81 dB Max working pressure 8 bar Max air consumption 330 l/min Capacity (free outlet 6 bar self-levelling grease at 20 °C) 1000 g/min Grease follower plate yes Grease coupler p/n 66740 Nipple p/n 66892	Delivery hose length	4 m - 1/4"	
Capacity every 10 cycles of lever - Pump p/n 62041 Compression ratio 50:1 Noise level 81 dB Max working pressure 8 bar Max air consumption 330 l/min Capacity (free outlet 6 bar self-levelling grease at 20 °C) 1000 g/min Grease follower plate yes Grease coupler p/n 66740 Nipple p/n 66892	Delivery hose	p/n 993.504	
Pump p/n 62041 Compression ratio 50:1 Noise level 81 dB Max working pressure 8 bar Max air consumption 330 l/min Capacity (free outlet 6 bar self-levelling grease at 20 °C) 1000 g/min Grease follower plate yes Grease coupler p/n 66740 Nipple p/n 66892	Max grease outlet pressure	350 ÷ 400 bar	
Compression ratio 50:1 Noise level 81 dB Max working pressure 8 bar Max air consumption 330 l/min Capacity (free outlet 6 bar self-levelling grease at 20 °C) 1000 g/min Grease follower plate yes Grease coupler p/n 66740 Nipple p/n 66892	Capacity every 10 cycles of lever	-	
Noise level 81 dB Max working pressure 8 bar Max air consumption 330 l/min Capacity (free outlet 6 bar self-levelling grease at 20 °C) 1000 g/min Grease follower plate yes Grease coupler p/n 66740 Nipple p/n 66892	Pump	p/n 62041	
Max working pressure 8 bar Max air consumption 330 l/min Capacity (free outlet 6 bar self-levelling grease at 20 °C) 1000 g/min Grease follower plate yes Grease coupler p/n 66740 Nipple p/n 66892	Compression ratio	50:1	
Max air consumption 330 l/min Capacity (free outlet 6 bar self-levelling grease at 20 °C) Grease follower plate yes Grease coupler p/n 66740 Nipple p/n 66892	Noise level	81 dB	
Capacity (free outlet 6 bar self-levelling grease at 20 °C) Grease follower plate Grease coupler p/n 66740 Nipple p/n 66892	Max working pressure	8 bar	
levelling grease at 20 °C) Grease follower plate Grease coupler p/n 66740 Nipple p/n 66892	Max air consumption	330 l/min	
Grease coupler p/n 66740 Nipple p/n 66892		1000 g/min	
Nipple p/n 66892	Grease follower plate	yes	
	Grease coupler	p/n 66740	
Grease gun p/n 66888	Nipple	p/n 66892	
	Grease gun	p/n 66888	
Packing No. 1 - 0,100 m3	Packing	No. 1 - 0,100 m3	
Weight 16,7 kg	Weight	16,7 kg	



OVERALL DIMENSIONS (mm)

