



ADVANCED FLUID  
MANAGEMENT SOLUTIONS

**RAASM S.p.a.**

Via Marangoni 33, 36022  
S. Zeno di Cassola (VI) Italy  
Tel. +39 0424 570891  
info@raasm.com

## P/N 33072

Pneumatic piston pump s. 600 for transferring oil and similar, R 1:1 - 23 l/min with Viton® seals and suction tube 940 mm for 180÷220 kg drums

### AREAS OF USE

Aeronautics, Agriculture, Automotive, Cleaning, Building and road construction, Manufacturing industry, Mining industry, Lube trucks and transports, Railway transport

### FEATURES

Flow rate	23 l/min
Ratio	1:1
Compatible fluids	oils, lubricants and similar
Suction tube upper body	aluminum
Suction tube	carbon steel
Air inlet connection	G 1/4" (f)
Fluid outlet connection	G 1/2" (f)
Air working pressure	6 ÷ 8 bar
Average air consumption	230 l/min
Noise level	81 dB
max deliverable oil viscosity	SAE 80
Bung adaptor	-
Suitable for drums or tanks	suitable for drums 180 ÷ 220 kg
Packing	No. 1 - 0,020 m3
Weight	6,2 kg



### OVERALL DIMENSIONS (mm)

