



ART. 1670016

Control equipment for centralized lubrication system

Control and management unit 115-230-400-600 V AC with start/stop button, allarm light, full light reservoir, trasparente window for motor operated pump s. C15S - C15P with electromagnetic discharging valve



FLUIDS

FRESH OIL | GREASE

SECTORS

AERONAUTIC | AGRICULTURE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | CHEMICAL INDUSTRY | MANUFACTURING INDUSTRY | MINING | CENTRALIZED LUBRICATION SYSTEM | SHIPPING AND OFFSHORE

Features	UM	Value
Suitable for pump		C15S - C15P
Voltage	V AC	200 ÷ 500
Power consumed	W	1500 max
Button start/stop		yes
Light allarm		yes
Light filling		-
Tank full light		-
Trasparent window		yes
Filling control		-
Protection rating		IP55
Working pressure	°C	-25 ÷ +60
Packing	N° - m ³	1 - 0,03
Net weight	kg	15,2 ÷ 15,4
Gross weight	kg	15,5 ÷ 15,7

RAASM SpA

via Marangoni 33, 36022 - S. Zeno di Cassola (VI) - ITALIA
Tel. 0039 0424 571111 - Fax. 0039 0424 571135

info@raasm.com - www.raasm.com

Copyright © 2020 All rights reserved to RAASM S.p.A.