



# ART. 180D/81

## Industrial pumps - s. 1800

Divorced pump s.1800, for oil and lubricants, with PU seals



|                |   |
|----------------|---|
| FLUIDS         | FRESH OIL   |
| SECTORS        | MANUFACTURING INDUSTRY   MINING   SHIPPING AND OFFSHORE |
| CERTIFICATIONS | ATEX (ZONE 2)   ATEX (ZONE 22)                          |

| Features                   | UM                  | Value                                 |
|----------------------------|---------------------|---------------------------------------|
| Flow rate                  | l/min               | 65                                    |
| Ratio                      |                     | 8:1                                   |
| Compatible fluids          |                     | oils, lubricants and similar products |
| Suction tube upper body    |                     | carbon steel                          |
| Suction tube               |                     | carbon steel                          |
| Air inlet connection       |                     | G 1/2" (f)                            |
| Fluid outlet connection    |                     | G 1.1/2" (f)                          |
| Max supply pressure        | bar                 | 8                                     |
| Max air consumption 8 bar  | m <sup>3</sup> /min | 4,2                                   |
| Noise level                | dB                  | 80                                    |
| Suitable for drums or tank |                     | modular                               |
| Packing                    | N° - m <sup>3</sup> | 1 - 0,20                              |
| Weight                     | kg                  | 56                                    |
| Dimensions (A-B-C)         | cm                  | 43 - 62,5 - 16,2                      |

RAASM SpA

via Marangoni 33, 36022 - S. Zeno di Cassola (VI) - ITALIA  
Tel. 0039 0424 571111 - Fax. 0039 0424 571135

info@raasm.com - www.raasm.com

Copyright © 2020 All rights reserved to RAASM S.p.A.