



ART. 2503000

Centralized lubrication system - multidelivery 25

Motor operated pump s. C25S for oil 230-400 V AC - 50 Hz - 275-480 V AC - 60 Hz 4 poles and 4 pumping elements, R 70:1, 10 litres reservoir and min level indicator



FLUIDS

FRESH OIL

SECTORS

AERONAUTIC | AGRICULTURE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | CHEMICAL INDUSTRY | MANUFACTURING INDUSTRY | MINING | CENTRALIZED LUBRICATION SYSTEM | SHIPPING AND OFFSHORE

| Features | UM | Value |
|-----------------------------|----------------------|---|
| Flow rate | cm ³ /min | 25 |
| Tank capacity | litres | 10 |
| Reducer ratio | | 70:1 |
| Lubricant inlet connection | | G 1/2" (f) |
| Lubricant outlet connection | | G 1/4" (f) |
| N° of pistons | | 4 |
| Working temperature | °C | -25 ÷ +60 |
| Compatible fluids | | oils > 40 cSt |
| Supply | | 230/400 V AC - 50 Hz - 275/480 V AC - 60 Hz |
| Velocity | | 4 poles: 1370 ÷ 1660 rpm |
| Packing | N° - m ³ | 1 - 0,141 |
| Net weight | kg | 31,1 |
| Gross weight | kg | 42,9 |

RAASM SpA

via Marangoni 33, 36022 - S. Zeno di Cassola (VI) - ITALIA
Tel. 0039 0424 571111 - Fax. 0039 0424 571135

info@raasm.com - www.raasm.com

Copyright © 2020 All rights reserved to RAASM S.p.A.