



ART. 2503465

Centralized lubrication system - multidelivery 25

Motor operated pump s. C25S for oil 230-400 V AC - 50 Hz - 275-480 V AC - 60 Hz 6 poles and 4 pumping elements, R 35:1, 10 litres reservoir and min level indicator



FLUIDS

FRESH OIL

SECTORS

AERONAUTIC | AGRICULTURE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | CHEMICAL INDUSTRY | MANUFACTURING INDUSTRY | MINING | CENTRALIZED LUBRICATION SYSTEM | SHIPPING AND OFFSHORE

Features	UM	Value
Flow rate	cm ³ /min	35
Tank capacity	litres	10
Reducer ratio		35:1
Lubricant inlet connection		G 1/2" (f)
Lubricant outlet connection		G 1/4" (f)
N° of pistons		4
Working temperature	°C	-25 ÷ +60
Compatible fluids		oils > 40 cSt
Supply		230/400 V AC - 50 Hz - 275/480 V AC - 60 Hz
Velocity		6 poles: 870 ÷ 1100 rpm
Packing	N° - m ³	1 - 0,141
Net weight	kg	31,1
Gross weight	kg	42,9

RAASM SpA

via Marangoni 33, 36022 - S. Zeno di Cassola (VI) - ITALIA
Tel. 0039 0424 571111 - Fax. 0039 0424 571135

info@raasm.com - www.raasm.com

Copyright © 2020 All rights reserved to RAASM S.p.A.