



ART. 2504320

Centralized lubrication system - multidelivery 25

Motor operated pump s. C25S for oil 230-400 V AC - 50 Hz - 275-480 V AC - 60 Hz 4 poles and 16 pumping elements, R 70:1, 30 litres reservoir and min level indicator



FLUIDS

FRESH OIL

SECTORS

AERONAUTIC | AGRICULTURE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | CHEMICAL INDUSTRY | MANUFACTURING INDUSTRY | MINING | CENTRALIZED LUBRICATION SYSTEM | SHIPPING AND OFFSHORE

Features	UM	Value
Flow rate	cm ³ /min	100
Tank capacity	litres	30
Reducer ratio		70:1
Lubricant inlet connection		G 1/2" (f)
Lubricant outlet connection		G 1/4" (f)
N° of pistons		16
Working temperature	°C	-25 ÷ +60
Compatible fluids		oils > 40 cSt
Supply		230/400 V AC - 50 Hz - 275/480 V AC - 60 Hz
Velocity		4 poles: 1370 ÷ 1660 rpm
Packing	N° - m ³	1 - 0,208
Net weight	kg	36,2
Gross weight	kg	48,4

RAASM SpA

via Marangoni 33, 36022 - S. Zeno di Cassola (VI) - ITALIA
Tel. 0039 0424 571111 - Fax. 0039 0424 571135

info@raasm.com - www.raasm.com

Copyright © 2020 All rights reserved to RAASM S.p.A.