




ART. 2A7/2677EAI

Diaphragm pumps - entirely in polypropilene

Diaphragm pump in polypropylene series PPB-1 with dual inlet, 1" flanges, membranes in EPDM, balls in acetal and seats in AISI 316 stainless steel



FLUIDS

WASTE OIL | FRESH OIL | ANTIFREEZE | WINDSHIELD FLUID | WATER | DIESEL FUEL | ADBLUE® | PAINT | CLEANING DETERGENT

SECTORS

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | CLEANING | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | CHEMICAL INDUSTRY | MANUFACTURING INDUSTRY | MINING | SHIPPING AND OFFSHORE

Features	UM	Value
Flow rate	l/min	145
Ratio		1:1
Max pressure	bar	8
Max cycles for minute	cpm	270
Delivery for cycles	litres	0,540
Max suction lift	m	dry column 5 - wet column 7,5
Max size pumpable solids	mm	3
Max working temperature	°C	65
Noise level	dB	78
Max air consumption	m ³ /min	1,1
Air working pressure	bar	2 ÷ 6
Air inlet connection		G 3/8" (f)
Air outlet connection (muffler)		G 3/4" (f)
Fluid inlet connection		dual inlet ANSI 150 - DIN PN 10 - JIS 10K 1" (25 mm) proneness to G 1.1/4"
Fluid outlet connection		(f) thread
Balls for inlet		ANSI 150 - DIN PN 10 - JIS 10K 1" (25 mm) proneness to G 1.1/4" (f) thread
Membranes		ball valve
Balls		EPDM
Seats		acetal
Packing	N° - m ³	AISI 316 stainless steel
Gross weight	kg	1 - 0,03 9,6

RAASM SpA

via Marangoni 33, 36022 - S. Zeno di Cassola (VI) - ITALIA
Tel. 0039 0424 571111 - Fax. 0039 0424 571135

info@raasm.com - www.raasm.com

Copyright © 2020 All rights reserved to RAASM S.p.A.