



ART. 3001120

Centralized lubrication system - progressive 30

Motor operated pump s. C30B15 for grease 24 V DC with 1 pumping element, 1,5 litres reservoir, min level indicator and analogic display



FLUIDS

GREASE

SECTORS

AERONAUTIC | AGRICULTURE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | CHEMICAL INDUSTRY | MANUFACTURING INDUSTRY | MINING | CENTRALIZED LUBRICATION SYSTEM | SHIPPING AND OFFSHORE

Features	UM	Value
Flow rate	cm ³ /min	4,27
Tank capacity	litres	1,5
Control type		analog
Delivery union		G 1/4" (f)
Tank filling		by hydraulic greaser
N° of pumping elements		1
Working temperature	°C	-25 ÷ +60
Lubricant		grease max NLGI 2
Supply		24 V DC
Packing	N° - m ³	1 - 0,024
Net weight	kg	5,2
Gross weight	kg	6,2

RAASM SpA

via Marangoni 33, 36022 - S. Zeno di Cassola (VI) - ITALIA
Tel. 0039 0424 571111 - Fax. 0039 0424 571135

info@raasm.com - www.raasm.com

Copyright © 2020 All rights reserved to RAASM S.p.A.