



ART. 3085680

Centralized lubrication system - progressive 30

Motor operated pump s. C30F for grease with 60 kg reservoir (internal \varnothing 360 ÷ 400 mm), R 50:1 and delivery pressure control assembly



FLUIDS

GREASE

SECTORS

AERONAUTIC | AGRICULTURE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | CHEMICAL INDUSTRY | MANUFACTURING INDUSTRY | MINING | CENTRALIZED LUBRICATION SYSTEM | SHIPPING AND OFFSHORE

| Features | UM | Value |
|-----------------------------|----------------------|-------------------|
| Flow rate | cm ³ /min | 1330 |
| Tank capacity | kg | 60 |
| Pressure ratio | | 50:1 |
| Air inlet connection | | G 1/4" (f) |
| Lubricant outlet connection | | G 3/8" (f) |
| Working temperature | °C | -25 ÷ +60 |
| Lubricant | | grease max NLGI 2 |
| Drum internal \varnothing | mm | 360 ÷ 400 |
| Pump(R 50:1) | P/N | 62174 |
| Drum cover | P/N | 10/532 |
| Membrane | P/N | 66400 |
| Packing | N° - m ³ | 2 - 0,076 |
| Net weight | kg | 11,2 |
| Gross weight | kg | 11,8 |

RAASM SpA

via Marangoni 33, 36022 - S. Zeno di Cassola (VI) - ITALIA
Tel. 0039 0424 571111 - Fax. 0039 0424 571135

info@raasm.com - www.raasm.com

Copyright © 2020 All rights reserved to RAASM S.p.A.