



ART. 3086490

Centralized lubrication system - progressive 30

Motor operated pump s. C30F for oil with 50 kg reservoir (external \varnothing 340 ÷ 385 mm), R 50:1 and delivery pressure control assembly



FLUIDS

FRESH OIL

SECTORS

AERONAUTIC | AGRICULTURE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | CHEMICAL INDUSTRY | MANUFACTURING INDUSTRY | MINING | CENTRALIZED LUBRICATION SYSTEM | SHIPPING AND OFFSHORE

Features	UM	Value
Flow rate	cm ³ /min	1330
Tank capacity	kg	50 ÷ 60
Pressure ratio		50:1
Air inlet connection		G 1/4" (f)
Lubricant outlet connection		G 3/8" (f)
Working temperature	°C	-25 ÷ +60
Lubricant		oils > 40 cSt
Drum internal \varnothing	mm	340 ÷ 385
Pump(R 50:1)	P/N	62174
Drum cover	P/N	10/533
Membrane	P/N	-
Packing	N° - m ³	2 - 0,076
Net weight	kg	9,1
Gross weight	kg	9,7

RAASM SpA

via Marangoni 33, 36022 - S. Zeno di Cassola (VI) - ITALIA
Tel. 0039 0424 571111 - Fax. 0039 0424 571135

info@raasm.com - www.raasm.com

Copyright © 2020 All rights reserved to RAASM S.p.A.