



ART. 33070

Pneumatic pumps for oil

Modular pneumatic piston pump s. 600 for transferring oil and similar, R 1:1 - 23 l/min with Viton® seals



FLUIDS

FRESH OIL | ANTIFREEZE | DIESEL FUEL

SECTORS

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | MANUFACTURING INDUSTRY | MINING

Features	UM	Value
Flow rate	l/min	23
Ratio		1:1
Compatible fluids		oils, lubricants and similar
Suction tube upper body		aluminum
Suction tube		carbon steel
Air inlet connection		G 1/4" (f)
Fluid outlet connection		G 1/2" (f)
Air working pressure	bar	6 ÷ 8
Average air consumption	l/min	230
Noise level	dB	81
max deliverable oil viscosity	SAE	80
Bung adaptor		-
Suitable for drums or tanks		modular
Packing	N° - m ³	1 - 0,006
Weight	kg	4,3
Dimensions (A-B-C)	cm	35,5 - 0 - 0

RAASM SpA

via Marangoni 33, 36022 - S. Zeno di Cassola (VI) - ITALIA
Tel. 0039 0424 571111 - Fax. 0039 0424 571135

info@raasm.com - www.raasm.com

Copyright © 2020 All rights reserved to RAASM S.p.A.