



ART. 33518

Diaphragm pumps - entirely in polypropilene

Diaphragm pump series PPB-12 in polypropylene with suction tube in stainless steel for tanks



FLUIDS

WASTE OIL | FRESH OIL | ANTIFREEZE | WINDSHIELD FLUID | WATER | DIESEL FUEL | ADBLUE® | PAINT | CLEANING DETERGENT

SECTORS

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | CLEANING | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | CHEMICAL INDUSTRY | MANUFACTURING INDUSTRY | MINING | SHIPPING AND OFFSHORE

Features	UM	Value
Flow rate	l/min	65
Ratio		1:1
Max pressure	bar	8
Max cycles for minute	cpm	350
Delivery for cycles	litres	0,188
Max suction lift	m	dry column 4,5 - wet column 7,5
Max size pumpable solids	mm	1,5
Max working temperature	°C	65
Noise level	dB	76
Max air consumption	m ³ /min	0,89
Working pressure	bar	2 ÷ 6
Air inlet connection		G 3/8" (f)
Air outlet connection (muffler)		G 3/4" (f)
Fluid inlet connection		G 3/4" (f) (G 1" (f) for drum)
Fluid outlet connection		G 1/2" (f)
Suction-delivery ball valve with spring		cylindrical ball valve
Membranes		EPDM
Balls		acetal
Seats		polypropylene and AISI 316 stainless steel
Bung adaptor	P/N	33434
Suction tube	mm	1240 - ø 34
Packing	N° - m ³	2 - 0,034
Gross weight	kg	12,58

RAASM SpA

via Marangoni 33, 36022 - S. Zeno di Cassola (VI) - ITALIA
Tel. 0039 0424 571111 - Fax. 0039 0424 571135

info@raasm.com - www.raasm.com

Copyright © 2020 All rights reserved to RAASM S.p.A.