



ART. 35161

Pneumatic pumps for oil

Pneumatic piston pump s. 600 for transferring oil and similar, R 3:1 - 14 l/min with NBR seals and extendable suction tube 1"



FLUIDS

FRESH OIL | ANTIFREEZE

SECTORS

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | MANUFACTURING INDUSTRY | MINING

Features	UM	Value
Flow rate	l/min	14
Ratio		3:1
Compatible fluids		oils, lubricants and similar
Suction tube upper body		aluminum
Suction tube		carbon steel
Air inlet connection		G 1/4" (f)
Fluid outlet connection		G 1/2" (f)
Air working pressure	bar	6 ÷ 8
Average air consumption	l/min	330
Noise level	dB	81
max deliverable oil viscosity	SAE	130
Bung adaptor		Standard
Suitable for drums or tanks		customisable 1"
Packing	N° - m ³	1 - 0,01
Weight	kg	5,0
Dimensions (A-B-C)	cm	28,5 - 22 - 4,2

RAASM SpA

via Marangoni 33, 36022 - S. Zeno di Cassola (VI) - ITALIA
Tel. 0039 0424 571111 - Fax. 0039 0424 571135

info@raasm.com - www.raasm.com

Copyright © 2020 All rights reserved to RAASM S.p.A.