



ART. 44065

Waste oil gravity and suction drainers

Combination air operated oil suction drainer 65 litre with transparent chamber



FLUIDS	WASTE OIL
SECTORS	AERONAUTIC AGRICULTURE AUTOMOTIVE LUBE TRUCK AND INDUSTRIAL VEHICLE BUILDING INDUSTRY AND ROAD CONSTRUCTION
CERTIFICATIONS	PRESSURE EQUIPMENT DIRECTIVE

Features	UM	Value
Tank capacity	litres	65
Max draining capacity	litres	52
Prechamber capacity	litres	8
Bowl capacity	litres	15
Air pressure for depressurisation	bar	6,5 ÷ 7
Depressurisation time	min	2
Noise level	dB	75
Suction speed	l/min	1,5 ÷ 2
Total suction capacity	litres	43 ÷ 45
Discharging/Suction hose	m	2/2
Max pressure for discharging	bar	0,5
Set of probes	P/N	45560
Packing	N° - m ³	3 - 0,330
Weight	kg	38,2
Dimensions (A-B-C)	cm	60 - 42 - 153
Dimensions (D)	cm	175

RAASM SpA

via Marangoni 33, 36022 - S. Zeno di Cassola (VI) - ITALIA
Tel. 0039 0424 571111 - Fax. 0039 0424 571135

info@raasm.com - www.raasm.com

Copyright © 2020 All rights reserved to RAASM S.p.A.