



ART. 62074

Grease pumps

Grease pump s. 600, R 50:1 - 1500 g/min, with suction tube 740 mm



FLUIDS

GREASE

SECTORS

AERONAUTIC | AGRICULTURE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | MANUFACTURING INDUSTRY | MINING | CENTRALIZED LUBRICATION SYSTEM

Features	UM	Value
Flow rate	l/min	1500 g/min
Ratio		50:1
Compatible fluids		greases, medium/high viscosity
Suction tube upper body		aluminum
Suction tube		carbon steel
Air inlet connection		G 1/4" (f)
Fluid outlet connection		G 3/8" (f)
Air working pressure	bar	6 ÷ 8
Average air consumption	l/min	330
Noise level	dB	81
Air max pressure	bar	8
Suitable for drums	kg	50 ÷ 60
Pump	P/N	-
Hose reels	P/N	-
Gun	P/N	-
Drum cover	P/N	-
Follower plate	P/N	-
Grease connection hose	P/N	-
Nipple	P/N	-
Drip-tray	P/N	-
Packing	N° - m ³	1 - 0,020
Weight	kg	6,1
Dimensions (A-B-C)	cm	26,5 - 74 - 3

RAASM SpA

via Marangoni 33, 36022 - S. Zeno di Cassola (VI) - ITALIA
Tel. 0039 0424 571111 - Fax. 0039 0424 571135

info@raasm.com - www.raasm.com

Copyright © 2020 All rights reserved to RAASM S.p.A.