

REWINDING BRAKE



No. 223-SC

**ADVANCED FLUID
MANAGEMENT SOLUTIONS**





**ADVANCED FLUID
MANAGEMENT SOLUTIONS**

Automatic rewinding





...discover the rewinding brake strength points



**ADVANCED FLUID
MANAGEMENT SOLUTIONS**

REWINDING BRAKE



STRENGTH POINTS



SLOWED REWINDING

The brake reduces the rewinding speed in case of accidental hose release. For this reason, it is possible for the operators to work in safer conditions avoiding unexpected breakages of the tools connected with the hose.



STURDY

Designed with black high resistance techno-polymer cover tested to withstand the impacts.



IP65

Entirely waterproof with IP65 protection degree.



STAINLESS STEEL

The stainless steel hose reel connection pin and screws are suitable for corrosive working environments.



5 MINUTES ASSEMBLY

Easy assembly both on new and already used models.
The valued assembly time is only 5 minutes.



AVAILABLE FOR S. 430-530-540-560

Available for all RAASM open hose reels series 430, 530, 540 and 560, in ABS, painted or stainless steel*.

* Hose reels for welding, GPL and methane and dual inlet-outlet are not available with the rewinding brake.

TECHNICAL CHARACTERISTICS


Visit our
website



MOLDED SEAL
to guarantee the
IP65 protection
degree.

**SHOCKPROOF
COVER**
in black high
resistance
techno-polymer.


FIXING SCREWS
in stainless steel.



Helpful hint



The rewinding brake components are not consumable and have a long lifetime. **RAASM suggests to lubricate the internal gears once a year** as indicated in the instruction manual.





REWINDING BRAKE

The new **RAASM brake** is designed to control the hose rewinding speed in the series 430, 530, 540 and 560 of all the open hose reels (included the swivelling version, the ABS and painted or stainless steel models)*.

The brake, thanks to an easy and fast assembly, is usable everywhere and from any operator. It guarantees a controlled and safety rewinding speed in case of accidental hose release.





✓ **Convenience
and safety**

* Hose reels for welding, GPL and methane and dual inlet-outlet are not available with the rewinding brake.

⚠ The hose reel equipped with the rewinding brake is not suitable for installation in potentially explosive atmosphere.

P/N 843021

Rewinding brake


Overall dimensions (mm)	Packaging (mm) W x D x H		Weight
		190 x 150 x 145	1,25 kg
	(W: width - D: depth - H: height)		

HOW TO INSTALL THE REWINDING BRAKE




In the suitable open **series 430** the rewinding brake can be mounted in the following positions:

1 Along the fixing bracket




2 180° rotated compared to the arm




SERIES
430

In the suitable open **series 530, 540 and 560** the rewinding brake can be installed as you like in the following three positions:


1 Along the fixing bracket



2 180° rotated compared to the arm



3 Along the arm



SERIES
530
540
560



■ Technology

The research and development of cutting-edge solutions, carried out entirely in Italy, is the starting point for the entire production cycle.



■ Quality

Offering high-quality products is one of our main objectives. Specific and rigorous tests accompany every single stage of the production process.



■ Efficiency

RAASM offers a complete range of fluid management solutions suitable for many different sectors of use. Our success is founded on the ability to identify and satisfy the specific needs of our customers.



Company with quality and environment system according to ISO 9001:2015 and ISO 14001:2015 standards

RAASM S.p.A.
36022 S. ZENO DI CASSOLA (VI)
Via Marangoni, 33 - ITALY

Export department
Tel. +39 0424 571130 - Fax +39 0424 571135

Technical department
Tel. +39 0424 571150 - Fax +39 0424 571155
info@raasm.com - www.raasm.com



WRV223SC-GB Rev 01

Authorized dealer

All rights reserved by Raasm S.p.A.