

WARNING TAPE REEL LIZARD

N° 223-AN

Surrounded by safety



**ADVANCED FLUID
MANAGEMENT SOLUTIONS**





P/N	Tape color	Length	Weight
92800.010	White - Red	16 m	5,7 kg
92800.020	Yellow - Black	16 m	5,7 kg


Overall dimensions of the delimitation tape	Width	Thickness	Length
 	40 mm	1,5 mm	16 m

△ Longer tape lengths are available on request

SPEED CONTROL

The versions listed below come with clutch so that tape rewinding can be performed at a controlled speed. They are marked by the **SPEED CONTROL** dataplate.

P/N	Tape color	Length	Weight
92840.010	White - Red	16 m	6,1 kg
92840.020	Yellow - Black	16 m	6,1 kg

Overall dimensions of the delimitation tape	Width	Thickness	Length
 	40 mm	1,5 mm	16 m

△ Longer tape lengths are available on request

STRENGTH POINTS

- AISI 304 stainless steel automatic hose guide suitable for potential corrosive atmospheres.
- Repeated spring stress-tests guarantee decades of life and efficiency.
- Speed control rewinding brake is available as accessory with specific P/N.
- Carabiner hook in aluminum as standard with the selected tape.
- White-red and yellow-black tapes available.
- Stopping pawl easy to remove for maintenance or when the work requires free sliding.
- Anti-shook technopolymer protecting cover.
- Fixing bracket that can be rotated up to 90° per side and with 2 slotted holes for safe, easy installation. The bracket can be locked in place with a screw, making the cable reel fixed.

ACCESSORY FOR WARNING TAPE REEL

P/N 89003
Bayonet bracket, lets you easily move the tape reel within the various workstations.



EXAMPLES OF WARNING TAPE REEL WITH ACCESSORIES



Company with quality and environment system according to ISO 9001:2015 and ISO 14001:2015 standards

Visit our website



RAASM S.p.A.

36022 S. ZENO DI CASSOLA (VI)
Via Marangoni, 33 - ITALY

Export department

Tel. +39 0424 571130
Fax +39 0424 571135

Technical department

Tel. +39 0424 571150
Fax +39 0424 571155

www.raasm.com
info@raasm.com

