

PRESSURE SPRAYERS FOR HYGIENIC ENVIRONMENTS



**ADVANCED FLUID
MANAGEMENT SOLUTIONS**






P/N 23024

P/N 23025

Devices for the non-toxic spraying of low viscosity detergent liquids, disinfectants and similar. Filled to 3/4 their capacity with the required liquid and pressurised with air at 6 - 8 bar, they work independently without requiring continuous connection to the compressed air line.

P/N	23024	23025
Surface treatment	Painted stainless steel	Polished stainless steel
Tank capacity	24 l	24 l
Fluids	Lubricants and detergents	
Delivery hose length	5 m	5 m
Max working pressure	8 bar	8 bar
Gun length	0,65 m	0,65 m
Safety valve	8 bar	8 bar
Level gauge	yes	yes
Spray gun	24806	24806
Spray nozzle	24801	24801
Antisplash funnel	24891	24891
Packing N° - m ³	1 - 0,090	1 - 0,090
Weight	12,8 kg	12,8 kg
Dimensions (A - B - C)	28 - 33 - 92 cm	28 - 33 - 92 cm

 May also use aggressive fluids (such as some acid solutions) if only compatible with the materials composing the device and after the RAASM technical approval.

STRENGTH POINTS

- Suitable for a wide range of cleaning and disinfection solutions
- 5 meters of spiral hose
- Comfortable 24 liter tank
- Antisplash Funnel included
- AISI 304 stainless steel full flow path available on request

EXAMPLE OF USE



Company with quality and environment system according to ISO 9001:2015 and ISO 14001:2015 standards

Visit our website



RAASM S.p.A.

36022 S. ZENO DI CASSOLA (VI)
Via Marangoni, 33 - ITALY

Export department

Tel. +39 0424 571130
Fax +39 0424 571135

Technical department

Tel. +39 0424 571150
Fax +39 0424 571155

www.raasm.com
info@raasm.com

